

MAILLON RAPIDE QUICK LINKS





Quick Links, or also commonly known as screw links, are gaining popularity for use in situations for which carabiners are not recommended, such as when tri-axial loading cannot be avoided. The Delta shape can be used to rig anchors. The Delta can be used as a chest harness connector. While slower to open and close than a carabiner, they can be more secure when tightened down — and they cost less.

Working-At-Height / Industrial Rope Access / Technical Rope Rescue

Working at height requires reliable, quality equipment. The Maillon Rapide Quick Links can be used with confidence in work-at-height maneuvers for industrial rope access or technical rope rescue when used in accordance with the regulatory safety standards they fall under. Always use life safety equipment and gear according to the regulatory safety standards for which it is classified and/or certified.

Option	Delta, 6 mm
Item	205002
PRODUCT WEIGHT	1.4 OZ (40 G)
BAR DIAMETER	6 MM
INSIDE LENGTH	1-3/4 IN (44 MM)
MATERIAL	STAINLESS STEEL
WORKING LOAD	4.4 KN (992 LBF)
BREAKING LOAD	22 KN (4950 LBF)
Option	Delta, 8 mm
Item	038208
PRODUCT WEIGHT	3 OZ (88 G)
BAR DIAMETER	8 MM

INSIDE LENGTH	57 MM (2.24 IN)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	5.4 KN (1,214 LBF)
BREAKING LOAD	27 KN (6,070 LBF)
Option	Delta, 10 mm
Item	382101
PRODUCT WEIGHT	5.3 OZ (150 G)
BAR DIAMETER	10 MM
INSIDE LENGTH	2-5/8 IN (67 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	8.8 KN (1,984 LBF)
BREAKING LOAD	44.1 KN (9,920 LBF)
Option	Delta, 12 mm
Item	382121
PRODUCT WEIGHT	9.1 OZ (258 G)
BAR DIAMETER	12 MM
INSIDE LENGTH	3-3/16 IN (81 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	10.8 KN (2,425 LBF)
BREAKING LOAD	53.9 KN (12,125 LBF)
Option	
	53.9 KN (12,125 LBF)
Option	53.9 KN (12,125 LBF) Oval, 5 mm
Option	53.9 KN (12,125 LBF) Oval, 5 mm 383051
Option Item PRODUCT WEIGHT	53.9 KN (12,125 LBF) Oval, 5 mm 383051 1.3 OZ (37 G)
Option Item PRODUCT WEIGHT BAR DIAMETER	53.9 KN (12,125 LBF) Oval, 5 mm 383051 1.3 OZ (37 G) 5 MM
Option Item PRODUCT WEIGHT BAR DIAMETER INSIDE LENGTH	53.9 KN (12,125 LBF) Oval, 5 mm 383051 1.3 OZ (37 G) 5 MM 1-9/16 IN (40 MM)
Option Item PRODUCT WEIGHT BAR DIAMETER INSIDE LENGTH MATERIAL	53.9 KN (12,125 LBF) Oval, 5 mm 383051 1.3 OZ (37 G) 5 MM 1-9/16 IN (40 MM) STAINLESS STEEL
Option Item PRODUCT WEIGHT BAR DIAMETER INSIDE LENGTH MATERIAL WORKING LOAD	53.9 KN (12,125 LBF) Oval, 5 mm 383051 1.3 OZ (37 G) 5 MM 1-9/16 IN (40 MM) STAINLESS STEEL 4.4 KN (992 LBF)

PRODUCT WEIGHT	1.8 OZ (51 G)
BAR DIAMETER	7 MM
INSIDE LENGTH	2-1/16 IN (52 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	5.4 KN (1,213 LBF)
BREAKING LOAD	27 KN (6,065 LBF)
Option	Oval, 12 mm
Item	383121
PRODUCT WEIGHT	8.2 OZ (233 G)
BAR DIAMETER	12 MM
INSIDE LENGTH	3-3/16 IN (81 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	14.7 KN (3,307 LBF)
BREAKING LOAD	73.6 KN (16,535 LBF)
Option	Long Oval, 10 mm
Item	384101
PRODUCT WEIGHT	5.6 OZ (159 G)
BAR DIAMETER	10 MM
INSIDE LENGTH	3-3/8 IN (86 MM)
MATERIAL	GALVANIZED STEEL
WORKING LOAD	9.8 KN (2,205 LBF)
BREAKING LOAD	49 KN (11,025 LBF)